



No measures are required.
 Useable with measures.
 Reduce exposure duration.

model	daily exposure time [h]	time sequence operating mode (idling/ full load/ nom. speed)	standard	equivalent vibration level handle left a hv,eq [m/s ²]	equivalent vibration level handle right a hv,eq [m/s ²]	daily vibration exposure handle left A(8) [m/s ²]	daily vibration exposure handle right A(8) [m/s ²]
BG 55	1,0	1/7 / - / 6/7	ISO 8662	10,4	7,2	3,7	2,5
BG 56 C-E-D	1,0	1/7 / - / 6/7	ISO 22867	7,5	6,3	2,7	2,2
BG 56 D	1,0	1/7 / - / 6/7	ISO 22867	7,5	6,3	2,7	2,2
BG 85	1,0	1/7 / - / 6/7	ISO 8662	13,0	8,5	4,6	3,0
BG 86 C-E-D	1,0	1/7 / - / 6/7	ISO 22867	1,8	1,5	0,6	0,5
BG 86 D	1,0	1/7 / - / 6/7	ISO 22867	1,8	1,5	0,6	0,5
SH 55	1,0	1/7 / - / 6/7	ISO 8662	10,3	7,7	3,6	2,7
SH 56 C-E-D	1,0	1/7 / - / 6/7	ISO 22867	7,5	6,3	2,7	2,2
SH 56 D	1,0	1/7 / - / 6/7	ISO 22867	7,5	6,3	2,7	2,2
SH 85	1,0	1/7 / - / 6/7	ISO 8662	13,0	8,5	4,6	3,0
SH 86 C-E-D	1,0	1/7 / - / 6/7	ISO 22867	1,8	1,5	0,6	0,5
SH 86 D	1,0	1/7 / - / 6/7	ISO 22867	1,8	1,5	0,6	0,5

All data is subject to change and applicable to European versions only.