



No measures are required.  
 Useable with measures.  
 Reduce exposure duration.

model	daily exposure time [h]	time sequence operating mode (idling/ full load/ nom. speed)	standard	equivalent vibration level handle left a hv,eq [m/s <sup>2</sup> ]	equivalent vibration level handle right a hv,eq [m/s <sup>2</sup> ]	daily vibration exposure handle left A(8) [m/s <sup>2</sup> ]	daily vibration exposure handle right A(8) [m/s <sup>2</sup> ]
BT 45 13mm, 1	1,0	1/5 / - / 4/5	ISO 8662	7,2	6,1	2,5	2,2
BT 45 13mm, 2	1,0	1/5 / - / 4/5	ISO 8662	7,2	7,5	2,5	2,7
BT 45 90mm	1,0	1/5 / - / 4/5	ISO 8662	12,0	7,0	4,2	2,5
BT 121 90mm	3,0	1/5 / - / 4/5	ISO 8662	2,2	2,5	1,3	1,5
BT 120 C 150mm	3,0	1/5 / - / 4/5	ISO 8662	8,7	7,4	5,3	4,5
BT 360	3,0	1/5 / - / 4/5	ISO 8662	9,0	8,9	5,5	5,5

All data is subject to change and applicable to European versions only.