



No measures are required.
 Useable with measures.
 Reduce exposure duration.

| model | daily exposure time [h] | time sequence operating mode (idling/ full load/ nom. speed) | standard | equivalent vibration level handle left a hv,eq [m/s ²] | equivalent vibration level handle right a hv,eq [m/s ²] | daily vibration exposure handle left A(8) [m/s ²] | daily vibration exposure handle right A(8) [m/s ²] |
|------------|-------------------------|--|----------|--|---|---|--|
| MM 55 -BF | 2,0 | 1/7 / - / 6/7 | EN 709 | 2,3 | 3,6 | 1,2 | 1,8 |
| MM 55 -BK | 2,0 | 1/7 / - / 6/7 | EN 709 | 2,3 | 3,6 | 1,2 | 1,8 |
| MM 55 -FCS | 2,0 | 1/2 / - / 1/2 | EN 709 | 2,4 | 3,4 | 1,2 | 1,7 |
| MM 55 -KB | 2,0 | 1/7 / - / 6/7 | EN 709 | 2,3 | 3,6 | 1,2 | 1,8 |
| MM 55 -KW | 2,0 | 1/7 / - / 6/7 | EN 709 | 2,3 | 3,6 | 1,2 | 1,8 |
| MM 55 -MF | 2,0 | 1/7 / - / 6/7 | EN 709 | 2,3 | 3,6 | 1,2 | 1,8 |
| MM 55 -RL | 2,0 | 1/7 / - / 6/7 | EN 709 | 2,3 | 3,6 | 1,2 | 1,8 |

All data is subject to change and applicable to European versions only.